

# Dolphin 7600

## Mobile Computer

The Dolphin 7600 device offers a range of features and functionality superior to other devices in its class. Combining the data collection and communication attributes of an industrial-grade mobile computer with a more compact design, the 7600 offers users the opportunity to deploy a powerful and reliable productivity tool.

The 7600 is perfect for the user that is constantly on the move. Its small, lightweight, and ergonomic design offers workers easy, comfortable, one-handed use as opposed to the heavy, bulky data collection devices that can cause worker fatigue and repetitive stress injuries.

To provide seamless data and voice communications, the 7600 features an integrated triple-radio design for Wireless Full Area Networking (WFAN™) technology – combining Bluetooth®, 802.11 and GSM/GPRS EDGE to provide reliable real-time information access and exchange anytime, anywhere. Full shift power management provides continuous and uninterrupted runtime, even when used in full time wireless, scan-intensive environments.

Powered by Adaptus® Imaging Technology 5.0, the 7600 delivers one of the broadest suite of advanced data capture capabilities, including linear and 2D bar code scanning, digital image capture, and intelligent signature capture, allowing users to increase efficiency and customer service.

Purpose-built for light industrial applications, the 7600 is ideal for use in retail, parcel delivery, postal, route accounting, field services, warehousing, and task management applications.



## Features

- **Small, Ergonomic Design:** Contoured, narrow body with an integrated finger saddle and angled image engine for comfortable one-handed use
- **Full Shift Power Management:** Powers an entire work shift of use, delivering uninterrupted data processing for enhanced worker productivity and reduced battery replacement costs
- **Versatile, High Performance Data Collection:** Adaptus Imaging Technology 5.0 reads linear and 2D bar codes and captures digital images, giving you the ability to process and manage more data with a single device than ever before
- **Windows Mobile® 6.0 or Windows® CE 5.0:** Powerful, industry standard platforms for developers and users, simplifying integration and ensuring intuitive operation
- **Engineered for Durability:** Constructed for reliable use in light industrial applications—in the field and on-site
- **Built-In GPS Technology:** Enables turn-by-turn navigation, driver route optimization, “bread-crumbling,” geo-fencing, and other location-based applications
- **Wireless Full Area Networking (WFAN) Technology:** Integrated WAN, LAN, and PAN for real-time data exchange and voice communications keeps users continually connected to mission critical information
- **Vibrant Color Display:** 2.8 in. ¼ VGA color display provides easy viewing and touch screen use
- **Backlit Numeric and Alpha Keyboards:** Strategic key placement enables efficient one-handed operation while the backlight increases usability in most lighting conditions

# Dolphin 7600 Technical Specifications

## System Architecture

|                         |   |
|-------------------------|---|
| CPU                     | Samsung 2440 400 MHz  |
| Operating System        | BT & BT/WLAN Configurations: Windows CE 5.0 or Windows Mobile 6 Classic<br>GSM Configurations: Windows Mobile 6 Professional  |
| Memory                  | 128MB RAM X 128MB Flash   |
| Display                 | 2.8 in. 1/4 VGA, 240 X 320, TFT color display with touch screen   |
| Storage Expansion       | Windows CE Configurations: User-accessible memory expansion slot for SD or MMC flash memory cards<br>Windows Mobile Configurations: User-accessible microSD™/microSDHC™ |
| Battery                 | Li-ion battery 3.7V / 2200 mAh / 8.1 Wh (standard) OR Li-ion battery 3.7V / 3240 mAh / 12.0 Wh (optional)   |
| Imager/Scanner          | 5300 Standard Range with High-Vis laser aimer   |
| Decode Capabilities     | Reads standard 1D and 2D symbologies. Visit <a href="http://www.honeywellaidc.com/symbologies">www.honeywellaidc.com/symbologies</a> for details.                       |
| Keypad                  | 29-key numeric keyboard with shifted alpha and six(6) programmable keys; backlit<br>38-key alpha keyboard with shifted numeric and two(2) programmable keys; backlit    |
| Audio                   | On-board speaker, microphone, and standard 2.5mm headset jack   |
| I/O Ports               | RS-232/USB connector, IrDA port   |
| Development Environment | Honeywell SDK for Windows Mobile 6.0  |
| Third Party Software    | SOTI MobiControl (remote device management), PowerNet™ Terminal Emulation (TNVT, 3270, 5250), and ITScriptNet™  |

## Wireless Connectivity

|               |   |
|---------------|---|
| WWAN          | Quad Band: GSM 850/900/1800/1900MHz, GSM release 99, EDGE multi-slot class 12, GPRS multi-slot class 12     |
| WLAN          | 802.11b/g   |
| WLAN Security | Wi-Fi Certified, WPA2, EAP, CCXv4, WEP, LEAP, TKIP, MD5, EAP-TLS, EAP-TTLS, WPA-PSK, PEAP                   |
| WPAN          | Bluetooth Class 2, version 1.2  |
| GPS           | Integrated GPS (Global Positioning System) receiver with internal antenna supporting SiRFstarIII technology |

## Physical & Environmental

|               |   |
|---------------|---|
| Dimensions    | BT & BT/WLAN Configurations: 7.0 in. long X 2.7 in. wide X 1.7 in. deep (17.8 cm. long X 6.9 cm. wide X 4.2 cm. deep); GSM Configurations: 7.1 in. long X 2.7 in. wide X 1.9 in. deep (18 cm. long X 6.9 cm. wide X 4.7 cm. deep) |
| Weight        | BT & BT/WLAN Configurations: Approximately 11.7 oz./332g; GSM configurations: Approximately 14.3 oz./406g   |
| Temperature   | Operating: 14° to 122°F (-10° to 50°C); Charging: 32° to 104°F (0° to 40°C)   |
| Humidity      | 95% humidity (non-condensing)   |
| Drop          | 5 ft. (1.5m) multiple drops to concrete, all axis, and across operating temperature range   |
| Sealing       | IP54 rating rated for blown dust and water intrusion  |
| ESD           | Air: +/- 12k Vdc, Direct: +/- 8k Vdc  |
| Environmental | Independently certified to meet IP54 standards for moisture and particle resistance; RoHS and WEEE compliant  |

## Regulatory & Compliance

|        |  |
|--------|--|
| Safety | cUL 60950, NOM, EN60950, BSMI CN14336, CCC GB4943, PSB, SIRIM<br>5300SR VGA Area Imager with High-Vis bracket aimer<br>Caution - use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure. |
| EMC    | FCC Part 15 Class B, ICES-003, EN301 489-1, EN301 489-17, EN55022, EN55024, BSMI CNS13438, CCC GB9254, MIC, AS/NZS 3548, FCC Parts 22H & 24H, FCC SAR OET 65, EN301511, RSS-132/133  |
| Radio  | US/Canada, R&TTE, FCC 15.247, RSS-210, COFE TEL, EN300 328-1, EN300 328-2, SRRRC ETS 300 328, IDA, SIRIM, MIC, ARIB STD-T33 & T66, AS/NZS 4771   |

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. Intel is a registered trademark of Intel Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.



For more information:  
[www.honeywellaidc.com](http://www.honeywellaidc.com)

## Honeywell Security & Data Collection

Honeywell Scanning & Mobility  
700 Visions Drive  
Skaneateles Falls, NY 13153  
800.582.4263  
[www.honeywell.com](http://www.honeywell.com)

